

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 340640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Richard Hintz - For: International Paper - 4/1978 - M 69-78

Set - 5/8" iron rod.
30" Fir stump bears N.4°00'E., 27.4 ft. scribed.
40" Fir bears N.85°00'W., 16.8 ft. scribed.

Ernesto R. Alvarado, USFS & Deputy, Douglas Co. Surveyor's
Office - Witness: Greg Martin - 3/20/1980 - C.S. File 61/6-13

Found - ½ machine axle with gear at top (no record)
36" D.Fir stump bears N.2°E., 28.39 ft. open face
scribing visible: ¼ BT. (Rec. 30" N.4°E., 27.4')
57" D.Fir bears N.87°W., 16.84 ft., partially healed
face, scribing: ¼ BT (Rec. N.85°W., 16.8 ft.)
Set - 2" Douglas Co. Surveyor brass cap on 1" steel pipe
mkd: T20S R10W C¼ S4 1980
¼ re-bar is inside 1" steel pipe & gear is deposited
alongside.

New Accessories:
New bearings & distances to found BTs.
36" D.Fir stump bears N.4°E., 28.5 ft.
57" D.Fir bears N.85°30'W., 16.8 ft.

Attention signs & boundary signs on metal fence posts placed
West & North of corner. Location: Take Burma Rd. to IP Rd.
#20-10-4.1 location poster on edge of Rd. approx. 0.1 mile
from junction with Rd. #20-10-3.3. Corner bears N.10°W., 150
ft. from poster & lies on North lope in clear cut.