

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 1 Page(s) 177)

-----  
Set post corner to secs. 27, 28, 33, & 34; from which  
A Vine Maple, 4" dia., bears N.25°E., 38 lks.  
A Vine Maple, 4" dia., bears S.65°E., 12 lks.  
A Vine Maple, 4" dia., bears S.35°W., 14 lks.  
A Maple, 20" dia., bears N.75°W., 124 lks.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11715)

-----  
Point for the cor. of secs. 27, 28, 33, & 34, at proportionate dist. longitudinally, with latitudinal position controlled by unofficial monumentation on line between secs. 28 Y 33 and the restored cor. of secs. 26, 27, 34, & 35. (See page 11737 for affidavit by Ray Dailey)  
Set an iron post, 3' long, 2" dia., 28" in the ground, with brass cap marked:  
T20S R10W  
S 28 S 27  
S 33 S 34  
1951

from which  
The corner post of an old fence, 14" dia., bears N.7°E., 102 lks.  
A Fir, 22" dia., bears S.4½°E., 402 lks., mkd: T20S R10W S34 BT.  
A Fir, 30" dia., bears S.10°45'W., 393 lks., mkd: T20S R10W S33 BT.  
A white warning sign post at S edge of road, bears N.22½°W.

From this point the iron tip of a pitchfork handle, ½ dia., 4" above ground, firmly in place, bears N.88°48'W., 9.34 chs., an unofficial monumentation on line bet. secs. 28 & 33.

Richard Hintz, PLS #497 - For: International Paper Co. - Oct. 1982 - M 93-28

-----  
Found - US GLO 1951 IP/BC.  
22" Fir stump bears S.4°30'E., 264.8 ft. (1951)  
30" Fir uproot bears S.11°W., 255 ft. (1951)  
Set - 28" Fir bears S.2°30'W., 250.6 ft. (scribed)