TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 1 Page(s) 178)

Set post for ¼ sec. corner; from which
An Alder, 15" dia., bears S.7°W., 117 lks.
An Alder, 18" dia., bears S.45°E., 10 lks.

Fd. & used on GLO survey by William Thiel under contract 260 dated April 17, 1877 - (DCSO records Vol. 1 Page(s) 191)

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11718-19)

Point for the ¼ sec. cor. of secs. 27 & 28, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked: ¼
S 28 S 27
1951
from which
A Fir, 60" dia., bears S.51¼°E., 46 lks., mkd: ¼ S27 BT.
A Fir, 24" dia., bears S.5½°W., 51 lks., mkd: ¼ S28 BT.