

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Thiel under contract 260 dated Aug. 18, 1877 - (DCSO records Vol. 1 Page(s) 192)

Set post for corner to secs. 21, 22, 27, & 28, from which
A Fir, 15" dia., bears S.76½°W., 23 lks.
A Fir, 16" dia., bears N.46°W., 12 lks.
A Fir, 14" dia., bears S.76°E., 9 lks.
A Fir, 12" dia., bears N.44°E., 62 lks.

Fd. & used on GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 231)

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11719)

The cor. of secs. 21, 22, 27, & 28, determined at the record bearing & dist. from each of the remaining orig. BTs, as follows:

- A Fir stump, 30" dia., bears S.76°E., 9 lks., with partial scribe marks visible on sliver of old blaze.
- A Fir, 36" dia., bears S.76½°W., 23 lks., with blaze opened & the marks burned.
- A Fir, 44" dia., bears N.46°W., 12 lks., with partial scribe marks visible on partly opened blaze.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S R10W

S 21 S 22
S 28 S 27
1951

from which

- A Fir, 9" dia., bears N.81°15'E., 45 lks., mkd: T20S R10W S22 BT.
- A Fir, 8" dia., bears S.69¼°E., 26 lks., mkd: T20S R10W S27 BT.
- A Fir, 28" dia., bears S.64°45'W., 40 lks., mkd: T20S R10W S28 BT.