TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 233)

Set post, 4 ft. long, 3½" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on W face; from which
An Alder, 7" dia., bears N.20°E., 40 lks., mkd: ¼ S BT.
A Maple, 6" dia., bears S.15°W., 27 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11721)

Point for the ¼ sec. cor. of secs. 21 & 22, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 21|S 22
1952

from which
A Fir, 60" dia., bears N.5°E., 38 lks., mkd: ¼ S22 BT.
A Fir, 50" dia., bears N.17°W., 52 lks., mkd: ¼ S21 BT.

Jerry Estabrook - For: Menasha Log Co. LLC & The Campbell Group LLC ITS Manager - May 2012 - M163-55 & C.S. 65/75-5

Found - A 1" iron pipe with 2½" brass cap mkd "¼ S21 S22 1952" Per BLM
A 60" fir stump with no visible marks and new tag bears N.05°E., 25.1'.
A 50" fir stump with healed face and new tag bears N.17°W., 34.3'.
New BTs- A 19" fir face scribed "W¼ S22 BT" with x-chop and tag bears S.77°E., 9.4' to a spike at side center
A 17" fir face scribed "E¼ S21 BT" with x-chop and tag bears S.17°W., 5.8' to a spike at side center