TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 235)

Set post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on W face; from which
An Alder, 4" dia., bears N.40°E., 61 lks., mkd: ¼ S BT.
A Maple, 7" dia., bears S.56°W., 75 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11723)

Point for the ¼ sec. cor. of secs. 15 & 16, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft long, 1" dia., 28" in the ground with brass cap marked:

¼
S 16|S 15
1952

from which
A Fir, 32" dia., bears S.18°E., 40 lks., mkd: ¼ S15 BT.
A Cedar 20, 8" dia., bears N.8°W., 20 lks., mkd: ¼ S16 BT.

Jerry Estabrook - For: Menasha Log Co. LLC & The Campbell Group LLC ITS Manager - May 2012 - M163-55 & C.S. 65/75-5

Found - A 1" iron pipe with 2½" brass cap marked "¼ S15 S16 1952" Per BLM
A 32" fir stump with visible scribe and new tag bears S.18°E., 26.4' to face.
A 20" cedar stump with no visible marks and new tag bears N.8°W 13.2'
New BTs- A 13" fir face scribed "W¼ S15 BT" with x-chop and tag bears N.73°E., 5.5' to a spike at side center
A 17" fir face scribed "W¼ S15 BT" with x-chop and tag bears S.7°E., 10.4' to a spike at side center.