

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 235)

-----  
Set post, 4½ ft. long, 4" sq., 24" in the ground, for cor. of secs. 9, 10, 15, & 16, marked T20S S10 NE, R10W S15 on SE, S16 on SW, S9 on NW face, with 4 notches on S and 3 on E edges; from which

- A Fir, 12" dia., bears N.20°E., 29 lks., mkd: T20S R10W S10 BT.
- A Hemlock, 9" dia., bears S.34°E., 71 lks., mkd: T20S R10W S15 BT.
- A Fir, 10" dia., bears S.45°W., 81 lks., mkd: T20S R10W S16 BT.
- A Fir, 15" dia. bears N.60°W. 15 lks. mkd: T20S R10W S9 BT

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951/Oct 1952 - (DCSO rec Vol 27 Pg 11724)

-----  
Point for the cor. of secs. 9, 10, 15, & 16 proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S R10W	
S 9	S 10
S 16	S 15
1952	

- A Fir, 36" dia., bears N.76°E., 12 lks., mkd: T20S R10W S10 BT.
- A Fir, 56" dia., bears S.24½°E., 13 lks., mkd: T20S R10W S15 BT.
- A Hemlock, 28" dia., bears S.76°W., 70 lks., mkd: T20S R10W S16 BT.
- An Alder, 20" dia., bears N.33°W., 36 lks., mkd: T20S R10W S9 BT.

W. Carey Weatherly - For: International Paper Co. - Aug. 1982 - C.S. 58/276-2

-----  
Found - 1½" galv. IP w/1952 BLM brass cap in good condition.  
36" D.Fir BT (BLM 1952) now a 36" stump with IPCo. tag reading S.77°W., 6.0 ft.  
56" D.Fir BT, face evident (BLM 1952) now a 56" stump with IPCo. tag reading N.28°W., 9.4 ft.  
28" Hemlock BT (BLM BT) now a 34" stump with IPCo tag N.75¼°E., 45.4 ft.  
20" Alder BT (BLM 1952) now a 20" stump.  
44" D.Fir stump with IPCo tag reading N.51°W., 57.0'  
Set - IPCo tag on 20" Alder stump BT, reads S.33°E., 23.8'  
cont.

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Jerry Estabrook - For: Menasha Log Co. LLC & The Campbell Group LLC ITS Manager - May 2012 - M163-55 & C.S. 65/75-5  
-----

- Found - A 2" iron pipe with 2½" brass cap marked "T20S R10W S9 S10 S15 & S16 1952. Per BLM
- A 36" fir stump with healed face and tag bears N.76°E., 7.9'
  - A 56" fir stump with healed face and tag bears S.24¼°E., 8.6'.
  - A 28" hemlock stump with rotten face bears S.76°W., 46.2'
- New BTs- A 12" fir face scribed "NE S16 BT" with x-chop and tag bears S.38°W. 22.5' to a spike at side center
- A 13" fir face scribed "SE S9 BT" with x-chop and tag bears N.61°W., 9.7' to a spike at side center