

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 236-7)

-----  
Set post, 4 ft. long, 4" sq., 24" in the ground, for cor. of secs. 24 & 3, 4, 9. & 10, marked T20S S3 NE, R10W S10 on SE, S9 on SW, S4 on NW face, with 5 notches on S and 3 on E edges; from which

- A Hemlock, 20" dia., bears N.24°E., 93 lks., mkd: T20S R10W S3 BT.
- A Fir, 10" dia., bears S.36°E., 72 lks., mkd: T20S R10W S10 BT.
- A Fir, 9" dia., bears S.51°W., 81 lks., mkd: T20S R10W S9 BT.
- A Fir, 7" dia., bears N.67°W., 97 lks., mkd: T20S R10W S4 BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11726-7)

-----  
Point for the cor. of secs. 3, 4, 9, & 10, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S R10W

<u>S 4 S 3</u>
S 9 S 10
1952

from which

- A double Alder, 34" dia., bears N.61½°E., 71 lks., mkd: T20S R10W S3 BT.
- A Fir, 10" dia., bears S.18°45'E., 36 lks., mkd: T20S R10W S10 BT.
- A Fir, 16" dia., bears S.32°W., 17 lks., mkd: T20S R10W S9 BT.
- A Fir, 14" dia., bears N.24°W., 46 lks., mkd: T20S R10W S4 BT.