

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 238)

Set post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on W face; from which

A Fir, 10" dia., bears N.61°W., 71 lks., mkd: ¼ S BT.

A Fir, 12" dia., bears S.70°E., 80 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11728-29)

Point for the ¼ sec. cor. of secs. 3 & 4, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 4 S 3
1952

from which

A Fir, 18" dia., bears N.56½°E., 36 lks., mkd: ¼ S3 BT.

A Fir, 60" dia., bears N.16°W., 10 lks., mkd: ¼ S4 BT.