

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 411200

PRIMARY CORNER DESCRIPTION MC Secs. 27 & 34

Alias 941020 Description Meander Cor. Rt. Bank Smith River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 1 Page(s) 177)

Set meander post on right bank; from which
A Vine Maple, 4" dia., bears N.55°E., 31 lks.
A Vine Maple, 3" dia., bears S.10°E., 7 lks.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11717)

N.88°48'W 66.25 chs.
Point for the wit. cor. to the meander cor. of secs. 27 & 34.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground,
with brass cap marked:

WC

T20S

MC $\frac{S\ 27}{S\ 34}$

1951 R10W

from which

An Alder, 12" dia., bears S.41°E., 51 lks., mkd. with an X at breast height & the letters BT at the base.

An Ash, 8" dia., bears N.60°45'W., 166 lks., mkd. with an X at breast height and the letters BT at the base.

The Witness corner is located at the top of a bank sloping SW with bedrock exposed.

67.50 chs.

True point for the meander cor. of secs. 27 & 34, at proportionate dist., falls in river; there is no remaining evidence of the orig. corner.