TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 434100

PRIMARY CORNER DESCRIPTION N. 1/4 cor. for Sec. 3 only, T21-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 12, 1867 (DCSO records Vol. 1 Page(s) 175)

Set post for ¼ sec. cor., from which
An Alder 6" dia., bears N.42°E., 20 lks. dist.
An Alder 5" dia., bears S.35°E., 15 lks. dist.

Tied Corner in GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 208)

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (Group #36) (surveyed 1919) - (DCSO records Vol. 1 Page(s) 255-56) and (Dup. Pgs. 1060-61)

Set an Iron post 3 ft. long, 1" dia., 26" in the ground for ¼ sec. cor. of sec. 3 only, with brass cap mkd. ¼ _____
S 3
1919

from which
A Maple 10" dia., bears S.22°E., 20 lks. dist. mkd. ¼ S3 BT
A Chittem 8" dia., bears S.56°W., 68 lks. dist. mkd. ¼ S3 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11670

The ¼ sec. cor. of sec. 3, T21S R10W, monumented with an iron post 1" dia., the top rusted off 6" above ground, with brass cap mkd. in 1919,
from which the 1919 bearing trees:
A Maple 12" dia., bears S.22°E., 20 lks. dist. with blaze cleanly healed.
A Cascara 10" dia., bears S.64°W., 68 lks. dist. with no scribe marks remaining on old blaze. (Rec. brg. S.56°W.)
In place of the old post, set an iron post 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd. _____
¼ S 3
1951

(Cont. Next Page)

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 434100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 3 only, T21-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

from which a new bearing tree:
A Fir 10" dia., bears S.41¼°W., 30 lks. dist. mkd. ¼ S3 BT
Deposit the old post at the base of the new iron post.

Fd. OK, Nov. 1983 by H. Pieske - M 95-59 A&B