

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. for Sec. 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (Group #36) (surveyed 1919) - (DCSO records Vol. 1 Page(s) 256) and (Dup. Pg. 1061)

-----  
Apportioned distance.  
Set an Iron post 3 ft. long, 1" dia., 26" in the ground for  
¼ sec. cor. of sec. 34 only, with brass cap mkd. ¼  $\frac{S\ 34}{1919}$

from which  
A Chittem 8" dia., bears N.10°E., 61 lks. dist. mkd. ¼ S34  
BT.  
A Fir 14" dia., bears N.6°W., 66 lks. dist. mkd. ¼ S34 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11669-70)

-----  
The ¼ sec. cor., monumented with an iron post, 1" dia., the top rusted off 6" above ground, with brass cap mkd. in 1919, from which the remaining 1919 bearing tree  
A Fir 26" dia., bears N.5°W., 66 lks. dist., plainly blazed and healed. (Rec. brg. N.6°W.)  
In place of the old post, set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd. ¼  $\frac{S\ 34}{1951}$

from which a new bearing tree  
A Fir 36" dia., bears N.8½°E., 97 lks. dist. mkd. ¼ S34 BT  
Deposit the old iron post at the base of the new iron post.

Fd. OK, Nov. 1983 by H. Pieske - M 95-59 A&B