

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 1 Page(s) 177)

Set post for ¼ sec. corner; from which
An Alder, 15" dia., bears S.7°W., 48 lks.
A Chittewood, 6" dia., bears N.20°E., 56 lks.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11716)

Point for the ¼ sec. cor. of secs. 27 & 34, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

	S 27
¼	S 34
	1951

from which
A Fir, 38" dia., bears N.21°E., 21 lks., mkd: ¼ S27 BT.
A double Maple, 50" dia., bears S.33½°E., 68 lks., mkd: ¼ S34 BT.

Fd. & used on BLM dependent resurvey by Harvey E. Wofford, Cadastral Surveyor, under Group # 1468, surveyed Oct. 1988 thru 1989 - (DCSO records Vol. 47 Page(s) 17826)