

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 234)

Set post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on N face; from which
A Fir, 11" dia., bears N.50°W., 63 lks., mkd: ¼ S BT.
A Hemlock, 9" dia., bears S.76°W., 74 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11722)

Point for the ¼ sec. cor. of secs. 15 & 22, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:
¼ S 15
S 22
1952

from which
A Hemlock, 20" dia., bears N.3°45'W., 13 lks., mkd: ¼ S15 BT.
A Hemlock, 28" dia., bears S.70°E., 69 lks., mkd: ¼ S22 BT.