

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 236)

Set post, 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor., mkd: 1/4 S on N face; from which

A Maple, 12" dia., bears N.17°W., 72 lks., mkd: 1/4 S BT.

An Alder, 6" dia., bears S.27°W., 43 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11725)

Point for the 1/4 sec. cor. of secs. 10 & 15, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

1/4 $\frac{S\ 10}{S\ 15}$
1952

from which

A Fir, 54" dia., bears N.72°E., 36 lks., mkd: 1/4 S10 BT.

A Maple, 14" dia., bears S.58°E., 26 lks., mkd: 1/4 S15 BT.