

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 237)

Set post, 4 ft. long, 3½" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on N face; from which
An Alder, 7" dia., bears N.27°W., 71 lks., mkd: ¼ S BT.
An Alder, 6" dia., bears S.34°E., 63 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11727)

Point for the ¼ sec. cor. of secs. 3 & 10, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:
¼ S 3
 S 10
 1952

from which
A Fir, 18" dia., bears N.89¼°W., 29 lks., mkd: ¼ S3 BT.
A Fir, 13" dia., bears S.18½°E., 31 lks., mkd: ¼ S10 BT.