

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only, T21-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (Group #36) (surveyed 1919) - (DCSO records Vol. 1 Page(s) 256-7) and (Dup. Pg. 1061)

Set an Iron post 3 ft. long, 2" dia., 24" in the ground for cor. of secs. 2 and 3, with brass cap mkd.

S 3 S 2
T21S R10W
1919

from which

- A Fir 40" dia., bears S.25°E., 50 lks. dist. mkd. T21S R10W S2 BT.
- A Fir 30" dia., bears S.72°W., 33 lks. dist. mkd. T21S R10W S3 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11669)

The Sec. cor., monumented with an iron post, 2" dia., 8" above ground, firmly set, mkd. and witnessed as described in the official record. The iron post is rusted nearly through; in its place,

Set an iron post 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S R 10 W
S 34

S 3 S 2
T 21 S R 10 W
1951

from which the 1919 bearing trees;

- A Fir 48" dia., bears S.25°E., 50 lks. dist. plainly blazed and healed.
- A Fir 40" dia., bears S.72°W., 33 lks. dist., plainly blazed and healed.

Deposit the old iron post at the base of the new iron post.