

PRIMARY CORNER DESCRIPTION MC East line Sec. 34

Alias 940005 Description Meander Cor. Left Bank Smith River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 1 Page(s) 175)

Smiths River, 152 lks. wide, runs West, & set meander post o left bank; from which

A Maple, 15" dia., bears S.10°E., 50 lks.

A Maple, 10" dia., bears S.15°W., 41 lks.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11699-700)

Point for the meander cor. of secs. 34 & 35, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

MC
S 34 S 35
T20S R10W
1951

from which

A Fir, 22" dia., bears S.20°E., 384 lks., mkd: T20S R10W S35 MC BT.

A Fir, 14" dia., bears S.23¼°W., 180 lks., mkd: T20S R10W S34 MC BT.

BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group # 1168, surveyed Sept./Dec. 1983 - (DCSO records Vol. 47 Page(s) 17823)

The meander corner of secs. 34 & 35, on the left bank of the Smith River, determined from the remaining BT mkd. by Tillman

A Fir, 42" dia., bears S.23¼°W., 180 lks., with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

MC
S 34 S 35
T20S R10W
1983

from which

An iron post, 28" long, 2½" dia., set 26" in the ground, for a reference monument, bears S.25°E., 80 lks., with brass cap mkd: MC S35 RM 1983 and an arrow pointing to the corner.