

PRIMARY CORNER DESCRIPTION MC East line Sec. 34

Alias 941010 Description Meander Cor. Rt. Bank Smith River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 1 Page(s) 175)

Set meander post on right bank; from which
A Vine Maple, 5" dia., bears N.15°W., 16 lks.
A Vine Maple, 3" dia., bears N.40°E., 8 lks.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11700)

Point for the ¼ sec. cor. of secs. 34 & 35, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft long, 1" dia., 8" in drilled hole in bedrock, in a mound of stone to top, with brass cap marked:
T20S R10W
S 34 S 35
MC
1951

from which
A Fir, 18" dia., bears N.61¼°E., 146 lks., mkd: T20S R10W S35 MC BT.
A Fir, 18" dia., bears N.83°W., 183 lks., mkd: T20S R10W S34 MC BT.

BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group # 1168, surveyed Sept./Dec. 1983 - (DCSO records Vol. 47 Page(s) 17823-4)

Point selected for the witness cor. to the meander cor. of secs. 34 & 35 on the right bank of Smith River. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
WC
T20S R10W
S 34 S 35
MC
1983

from which
A Fir, 11" dia., bears N.23½°E., 82 lks., mkd: X BT.
An Alder, 12" dia., bears N.84°W., 39 lks., mkd: X BT.