

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 1 Page(s) 175-76)

Set post for ¼ sec. cor; from which
 An Alder, 3" dia., bears N.70°W., 3 lks.
 An Alder, 5" dia., bears N.45°E., 7 lks.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11700-01)

The ¼ sec. cor. of secs. 34 & 35, locally re-monumented with an iron pipe, 28" long, 1" dia., driven 2 ft. in the ground; another iron pipe, 40" long, 1" dia., has been driven 18" into the ground alongside to mark the point in the undergrowth; Douglas Dailey told me that he saw a cedar post, bearing scribe marks lying on the ground just downhill from this point many years ago, and that the position monumented has been locally accepted as the corner point for many years. At the corner point

Set an iron post, 3' long, 1" dia., 28" in the ground, with brass cap marked:

$\frac{1}{4}$
 S 34 | S 35
 1951

from which

Geological Survey GWM56 35 ft. above sea level, bears S.72°22'W., 44.09 chs.; a bronze tablet, 3½" dia., set in sandstone boulder, 44x26x16 ins. at S. side of road.

A Fir, 40" dia., bears S.1½°E., 9 lks., which I mark ¼ S35 BT. This tree bears a healed blaze facing the corner point, and has a very old X cut into the South side facing the road.

A Fir, 40" dia., bears N.30½°W., 111 lks., mkd: ¼ S34 BT. Reset the 2 iron pipes alongside the iron post.

BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group # 1168, surveyed Sept./Dec. 1983 - (DCSO records Vol. 47 Page(s) 17824)

Point for the ¼ sec. cor. of secs. 34 & 35, determined by the irregular boundary method; there is no remaining evidence of the orig. corner.

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked:

T20S R10W
 S 34 | S 35
 1983

(Cont. next page)

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which
A Fir, 8" dia., bears N.71½°E., 111 lks., mkd: ¼ S35 BT.
A Fir, 10" dia., bears N.80 3/4°W., 54 lks., mkd: ¼ S24 BT
Set a steel fence post, 5½ ft. long, alongside iron post.
From this point, a corner established by person(s) unknown,
bears N.39°53'W., 0.254 chs., monumented with an iron pipe,
1" dia., firmly set, projecting 12" above ground.

Fd. Ok by Baker, 3/11/1987 - CS File 63/50-25

Fd. & used on BLM dependent resurvey by Harvey E. Wofford,
Cadastral Surveyor, under Group # 1468, surveyed Oct. 1988
thru 1989 - (DCSO records Vol. 50 Page(s) 19104)