

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 1 Page(s) 176)

Set stone, 17x12x4, for corner to secs. 26, 27, 34, & 35; from which
A Chittewood, 6" dia., bears N.55°E., 33 lks.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11701)

Point for the cor. of secs. 26, 27, 34, & 35, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S R10W

S 27 S 26

S 34 S 35

1951

from which

A Maple, 30" dia., bears N.88°45'E., 105 lks., mkd: T20S R10W S26 BT.

A Cedar, 60" dia., bears S.15½°E., 140 lks., mkd: T20S R10W S35 BT.

A Cedar, 24" dia., bears S.27°W., 62 lks., mkd: T20S R10W S34 BT.

A Cedar, 32" dia., bears N.80½°W., 24 lks., mkd: T20S R10W S27 BT.

Fd. & used on BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group # 1168, surveyed Sept./Dec. 1983 - (DCSO records Vol. 47 Page(s) 17825)

Fd. & used on BLM dependent resurvey by Harvey E. Wofford, Cadastral Surveyor, under Group # 1468, surveyed Oct. 1988 thru 1989 - (DCSO records Vol. 50 Page(s) 19100-01)