

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Thiel under contract 260 dated April 17, 1877 - (DCSO records Vol. 1 Page(s) 192)

Set ¼ sec. post, being a Fir, 60" dia., ; from which
A Fir, 12" dia., bears S.16°E., 36 lks.
A Fir, 14" dia., bears S.30°W., 40 lks.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11703)

The ¼ sec. cor. of secs. 26 & 27, marked with a blaze in the bark on the East side of a Fir, 72" dia., scribed ¼ S; the positions of the orig. BTs indicated that this is the true corner point; from which

A dead Fir, 20" dia., bears S.16°E., 36 lks., plainly blazed & healed.

A Fir, 28" dia., bears S.30°W., 40 lks., plainly blazed & healed.

The corner tree being apparently sound, I reblaze it & mark ¼ S27 on W and S26 on E face, without disturbing the orig. blaze, and mark a new BT as follows:

A Fir, 35" dia., bears N.31¼°E., 79 lks., mkd: ¼ S26 BT.