

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William Thiel under contract 260 dated Aug. 17, 1877 - (DCSO records Vol. 1 Page(s) 193)

-----  
Set post for corner to secs. 22, 23, 26, & 27; from which  
A Fir, 12" dia., bears S.42½'E., 46 lks.  
A Fir, 42" dia., bears S.75½'W., 38 lks.  
A Fir, 48" dia., bears N.60'W., 38 lks.  
A Vine Maple, 4" dia., bears N.34½'E., 6 lks.

Fd. & used on GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 220)

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11703-4)

-----  
The cor. of secs. 22, 23, 26, & 27; determined at the record bearing & dist. from each of the orig. BTs, as follows;  
A Vine Maple stool, bears N.31½'E., 6 lks. with no blaze remaining.  
A Fir, 26" dia., bears S.42½'E., 46 lks. plainly blazed & healed.  
An uprooted Fir, 66" dia., the stump hole of which bears S.75½'W., 38 lks. with blaze underneath the trunk.  
A Fir, 66" dia., bears N.60'W., 38 lks. plainly blazed & healed.

At the corner point  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S R10W

S 22 S 23  
S 27 S 26  
1951

from which new BTs:

A Fir, 66" dia., bears N.15½'E., 36 lks., mkd: T20S R10W S23 BT.

A Fir, 50" dia., bears S.32'45'W., 72 lks., mkd: T20S R10W S27 BT.

The sec. cor. is located at the top of a spur, which slopes East.