

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 226)

Set post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on W face; from which

A Fir, 8" dia., bears N.15°E., 63 lks., mkd: ¼ S BT.

A Hemlock, 10" dia., bears S.30°E., 72 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11705)

Point for the ¼ sec. cor. of secs. 22 & 23, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 22 S 23
1951

from which

A Fir, 68" dia., bears N.54°W., 48 lks., mkd: ¼ S22 BT.

A Fir, 48" dia., bears S.25½°E., 84 lks., mkd: ¼ S23 BT.