

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 227-8)

Set post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on W face; from which

A Dogwood, 4" dia., bears N.40°E., 27 lks., mkd: ¼ S BT.

A Maple, 10" dia., bears S.60°W., 43 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11707-8)

Point for the ¼ sec. cor. of secs. 14 & 15, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 15 S 14
1952

from which

A Yew, 16" dia., bears N.12°E., 21 lks., mkd: ¼ S14 BT.

A Fir, 22" dia., bears N.83½°W., 65 lks., mkd: ¼ S15 BT.