

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 229)

-----  
Set post, 4½ ft. long, 4" sq., 24" in the ground, for cor. of secs. 2, 3, 10 & 11, marked T20S S2 NE, R10W S11 on SE, S10 on SW, S3 on NW face, with 5 notches on S and 2 on E edges; from which

- A Fir, 30" dia., bears N.73°E., 70 lks., mkd: T20S R10W S2 BT.
- A Fir, 25" dia., bears S.61°E., 80 lks., mkd: T20S R10W S11 BT.
- A Fir, 20" dia., bears S.27°W., 75 lks., mkd: T20S R10W S10 BT.
- A Fir, 22" dia., bears N.44°W., 87 lks., mkd: T20S R10W S3 BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11710)

-----  
Point for the cor. of secs. 2, 3, 10, & 11, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S R10W

S 3 S 2  
S 10 S 11  
1952

from which

- A Fir, 40" dia., bears N.71°45'E., 44 lks., mkd: T20S R10W S2 BT.
- A Yew, 7" dia., bears S.34°E., 41 lks., mkd: T20S R10W S11 BT.
- A Fir, 40" dia., bears S.27¼°W., 30 lks., mkd: T20S R10W S10 BT.
- A Yew, 6" dia., bears N.37°W., 75 lks., mkd: T20S R10W S3 BT.