

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 231)

-----  
Set post, 4 ft. long, 3½" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on W face; from which

A Fir, 16" dia., bears N.85°E., 100 lks., mkd: ¼ S BT.

A Fir, 12" dia., bears S.71°W., 86 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11712)

-----  
Point for the ¼ sec. cor. of secs. 2 & 3, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼  
S 2 S 3  
1952

from which

An Alder, 16" dia., bears N.53°E., 37 lks., mkd: ¼ S2 BT.

A Fir, 36" dia., bears N.83¼°W., 61 lks., mkd: ¼ S3 BT.