

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 220)

Marked a Chittem tree, 6" dia., for 1/4 sec. cor. mkd: 1/4 S on N face; from which a

- A Fir, 10" dia., bears N.55°W., 4 lks., mkd: 1/4 S BT.
- A Fir, 6" dia., bears S.60°E., 170 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11704)

Point for the 1/4 sec. cor. of secs. 23 & 26, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground, and in a mound of stone, 3 ft. base, to top with brass cap mkd:

1/4 $\frac{S\ 23}{S\ 26}$
1951

from which

- A Hemlock, 14" dia., bears N.44 1/4°E., 100 lks., mkd: 1/4 S23 BT.
- A Hemlock, 14" dia., bears S.16°E., 99 lks., mkd: 1/4 S26 BT.