TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 227)

Set post, 4 ft. long, 3½" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on N face; from which
A Fir, 12" dia., bears S.60°E., 71 lks., mkd: ¼ S BT.
A Fir, 9" dia., bears N.23°E., 80 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11706)

Point for the ¼ sec. cor. of secs. 14 & 23, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ S 14 / S 23 1951

from which
An Alder, 20" dia., bears N.79°W., 67 lks., mkd: ¼ S14 BT.
An Alder, 16" dia., bears S.53°E., 31 lks., mkd: ¼ S23 BT.

Jerry Estabrook - For: Roseburg Resources - 10/2021 - M180-12

FOUND - A 1" iron pipe with 2½" brass cap (properly) marked per BLM plat #1398. Set steel post alongside.
An 18" alder with visible bark scribe and tag bears S.53°E., 20.46'.

New BTs- A 17" Alder, bark scribed "S¼ S14 BT" with X-chop & tag bears N.53°E. 21.6' to a spike at side center
A 16" Alder, bark scribed "N¼ S23 BT" with X-chop & tag bears South 8.2' to a spike at side center
A 16" Alder, bark scribed "N¼ S23 BT with X-chop & tag bears S.70°W. 16.6' to a spike at side center

Note - LAT and LONG per GARMIN ETREX HAND HELD GPS: N.43°49'24.4" W.123°51'25.3"