TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 228-9)

Set post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on N face; from which
A Maple, 9" dia., bears N.44°W., 40 lks., mkd: ¼ S BT.
An Alder, 6" dia., bears S.50°W., 60 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11709)

Point for the ¼ sec. cor. of secs. 11 & 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ S 11 / S 14 1952

from which
A Hemlock, 20" dia., bears N.31°W.,37 lks., mkd: ¼ S11 BT.
A Hemlock, 18" dia., bears S.11½°W., 39 lks. mkd: ¼ S14 BT

Jerry Estabrook - For: Roseburg Resources - 10/2021 - M180-12

Found - A 1" iron pipe with 2½" brass cap (properly) marked per BLM Plat #1398.
An 18" Hemlock stump with visible scribe in open face bears S.11°30'W., 25.74'.
New BTs- An 8" Fir, face scribed "S¼ S11 BT" with X-chop and tag bears N.27°E., 11.7' to a spike at side center.
A 11" Fir, face scribed "N¼ S14 BT" with X-chop and tag bears S.69°E., 8.8' to a spike at side center.
A 9" Fir face scribed "N¼ S14 BT" with X-chop and tag bears S.6°E., 17.7' to a spike at side center.
A 13" Fir, face scribed "N¼ S14 BT" with X-chop and tag bears S.40°W., 2.8' to a spike at side center
Note - LAT and LONG per GARMIN ETREX HAND HELD CPS:
N. 43°50'13.2" W. 123°51'25.3"