

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 230)

Set post, 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor., mkd: 1/4 S on N face; from which

A Fir, 12" dia., bears N.53°W., 84 lks., mkd: 1/4 S BT.

A Fir, 10" dia., bears S.45°E., 78 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11711)

Point for the 1/4 sec. cor. of secs. 2 & 11, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

1/4 $\frac{S \ 2}{S \ 11}$
1952

from which

An Alder, 19" dia., bears N.84 1/4°E., 49 lks., mkd: 1/4 S2 BT.

A Cedar, 60" dia., bears S.86°W., 81 lks., mkd: 1/4 S11 BT.