

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 209)

-----

Set post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 35, 36, 1 & 2, marked T20S S36 on NE.; T21S R10W S.1 on SE.; T21S S2 on SW.; and S35 on NW. faces, with 5 notches on W. and 1 on E. edges; from which a

Fir 18" dia., bears N.44°E., 36 lks. dist. mkd. T20S R10W S36 BT.

Fir 14" dia., bears S.72½°E., 38 lks. dist. mkd. T21S R10W S1 BT.

Fir 12" dia., bears S.40°W., 50 lks. dist. mkd. T21S R10W S2 BT.

Fir 18" dia., bears N.27½°W., 14 lks. dist. mkd. T20S R10W S35 BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (Group #36) (surveyed 1919) - (DCSO records Vol. 1 Page(s) 258-59) and (Dup. Pg. 1064)

-----

Intersect the old cor. of secs. 1, 2, 35 and 36, which is a decayed post, mkd. and witnessed as described by the surveyor general. I change this cor. to refer to secs. 35 & 36 only and obliterate the marks on the old SE. and SW. bearing trees and alongside the old post, Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. to secs. 35 & 36, with brass cap mkd:

T20S	R10W
S35	S36
-----	
1919	

from which

A Fir 18" dia., bears N.44°E., 36 ks. dist. mkd. T20S R10W S36 BT. (Old BT)

A Fir 18" dia., bears N.27½°W., 14 lks. dist., mkd. T20S R10W S35 BT. (Old BT)

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11666)

-----

The cor. of secs. 35 & 36, monumented with an iron post 2" dia., the top rusted off 6" above ground with brass cap mkd. in 1918, from which 1892 bearing trees:

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Hemlock 22" dia., bears N.46°E., 36 lks. dist., with partial scribe marks visible on partly overgrown blaze. (Rec. description, a Fir 18" dia., N.44°E.)  
 A Fir 20" dia., bears N.30½°W., 13 lks. dist. with old blaze healed. (Rec. desc., N.27½°W., 14 lks. dist.)  
 In place of old post, set an iron post, 3 ft. long, 2" dia., 28" in the ground with brass cap mkd:

T 20 S R 10 W
S 35   S 36
T 21 S R 10 W
S 2
1951

Deposit old iron post at base of new iron post.

Douglas Co. Surveyors Office - Gary Langlitz; Clell Goodwin; Lenora Ladig; Vic Cangie - Nov. 12, 1975 - C.S. File 57/39-6  
 -----  
 Found - US GLO brass cap, 1951, properly marked.  
 The 1892 bearing trees noted during the 1951 resurvey are both down. We find them to be in their record positions.  
 New BTs- A 31" D.Fir bears West, 30.2 ft. scribed "T20S R10W S35 CS BT" on a double blaze.  
 A 25" Hemlock bears N.37°W., 31.9 ft. scribed "T20S R10W S35 CS BT" on a double blaze.  
 The NE. cor. of Sec. 2, T21-10, bears S.89°15'E., 86.5 ft. This cor. is located on top of a ridge at the SW. cor. of a clear cut unit.

Fd. OK, March 11, 1987 by D. Baker - C.S. File 63/50-24

BLM Resurvey by Harvey Wofford, Cadastral Surveyor, under Group #1468, surveyed Oct. 1988/June 1989 - (DCSO records Vol. 50 Page(s) 19095)  
 -----  
 Beginning at the cor. of secs. 35 and 36 only, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. in 1951,  
 from which the remains of an original bearing tree  
 A root hole, bears N. 46° E., 36 lks. dist., alongside of which is lying the remains of a burned hemlock, size indeterminate, no marks visible on burned blaze.  
 and the remains of bearing trees mkd. by Gary L. Langlitz,  
 A burned, sawed fir stump, 32 ins. diam., bears West, 45½ lks. dist., with scribe marks 20 10 35 BT visible on partially healed blaze.  
 (Cont. Next Page)

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A burned, sawed hemlock stump, 26 ins. diam., bears  
N. 37° W., 48½ lks. dist., with scribe marks T20S R10  
S35 CS BT visible on partially healed blaze.  
No other suitable trees available.