

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 217-8)

-----  
Set post, 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor., mkd: 1/4 S on W face; from which  
A Hemlock, 36" dia., bears S.20°W., 21 lks., mkd: 1/4 S BT.  
A Fir, 6" dia., bears S.41°W., 200 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11687)

-----  
Point for 1/4 sec. cor. of secs. 35 & 36, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3' long, 1" dia., 28" in the ground, with brass cap marked:

1/4  
S 35 S 36  
1951

from which

A Hemlock, 24" dia., bears S.33°E., 41 lks., mkd: 1/4 S36 BT.  
A Hemlock, 12" dia., bears S.23°W., 73 lks., mkd: 1/4 S35 BT.

Ronald Stuntzner - For: International Paper Co. - Oct. 19, 1984 - M 97-80

-----  
Found - 1951 GLO proportioned corner, 1" IP with 2 1/2" brass cap.

24" Hemlock now 30", S.33°E., 41 lks., (tagged with visible scar)

New BT - 8" Hemlock bears N.38°E., 12.8 ft., (faced with no scribe and tagged)

Note - 1951 SW BT lost in logging road construction.

BLM dependent resurvey by Harvey E. Wofford, Cadastral Surveyor, under Group # 1468, surveyed Oct. 1988 thru 1989 - (DCSO records Vol. 50 Page(s) 19097-98)

-----  
The 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd. T20S R10W

1/4  
S 35 S 36  
1951

(Cont. next page)

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which a bearing tree mkd. by Tillman  
A hemlock, 32 ins. diam., bears S. 33° E., 41 lks. with  
scribe marks 36 BT visible on partially healed blaze.  
and a bearing tree mkd. by Stuntzner, in 1984  
A hemlock, 9 ins. diam., bears N. 38° E., 19½ lks., with  
healed blaze.  
From this point, the BLM Geodetic Control Station No.  
EC41019, at latitude 43° 48' 20.902" N., longitude 123° 50'  
25.595" W. (NAD 1927), determined by the NAVSTAR GPS, bears  
N. 17° 44' 21" E., 94.391 chs., monumented with an aluminum  
cap, firmly set flush in a concrete pad, 1 ft. diam., with  
fiberglass post alongside. The cap is mkd. EC41019 GPS 1989.  
The corner is located at edge of timber, bears E. & S. 5° W.