

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 1 Page(s) 176)

 Set post for corner to secs. 25, 26, 35, & 36; from which
 A Fir, 30" dia., bears N.50°E., 20 lks.
 A Fir, 4" dia., bears S.67°E., 26 lks.
 A Vine Maple, 3" dia., bears S.50°W., 21 lks.
 A Vine Maple, 5" dia., bears N.42°W., 26 lks.

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 217)

 Intersect E & W line at point 45 lks., W of cor. of secs. 35, 36, 25, & 26, as determined by orig. BTs. The old post being destroyed, renewed the cor. by setting a post, 4 ft. long, 4" sq. 24" in ground, mkd: T20S S25 on NE, R10W S36 on SE, S35 on SW, S26 on NW face, 1 notch on S & E edges; from which
 A Fir, 36" dia., bears N.50°E., 20 lks., mkd: T20S R10W S25 BT.
 A Fir, 4" dia., bears S.67°E., 26 lks., mkd: T20S R10W S36 BT.
 A Maple, 4" dia., bears S.50°W., 21 lks., mkd: T20S R10W S35 BT.
 A Maple, 5" dia., bears N.42°W., 26 lks., mkd: T20S R10W S26 BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11687-8)

 The corner of secs. 25, 26, 35, & 36, determined at the record bearing & dist. from the orig. NE BT, as follows:
 A Fir, 60" dia., bears N.50°E., 20 lks., with partial scribe marks visible on old bark blaze.
 A sawed Fir stump, 70" dia., bears S.67°E., 26 lks.,, at the rec. position of the orig. SE BT, which was described as a Fir, 4" dia.; the stump shows traces of a bark blaze on the NW face and a count of the annual rings shows that it was approx. 40" dia., in 1867, rather than 4".
 At the corner point
 Set an iron post, 3' long, 2" dia., 28" in the ground, with brass cap marked:

T20S	R10W
S 26	S 25
S 35	S 36
1951	

 (Cont. next page)

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs 25, 26, 35, & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

from which new BTs
A Fir, 80" dia., bears S.12°E., 140 lks., mkd: T20S R10W S36 BT.
A Maple, 16" dia., bears S.12°W., 69 lks., mkd: T20S R10W S35 BT.
An Alder, 16" dia., bears N.75°15'W., 48 lks., mkd: T20S R10W S26 BT.

Fd. Ok by R. Stuntzner, 10/1984 - M 97-80

BLM dependent resurvey by Harvey E. Wofford, Cadastral Surveyor, under Group # 1468, surveyed Oct. 1988 thru 1989 - (DCSO records Vol. 50 Page(s) 19098-99)

The cor. of secs. 25, 26, 35, & 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 16" above ground, with brass cap mkd.
T20S R10W
S 26 | S 25
S 35 | S 36
1951

from which the remains of the original bearing trees
A fir, 62 ins. diam., bears N.50°E., 23 lks., with illegible scribe marks on bark blaze. (Record, 20 lks.)
A sawed fir stump, size indeterminate, bears S.67°E., 26 lks., no marks visible.
and the remains of the bearing trees mkd. by Tillman.
A sawed fir stump, size indeterminate, bears S.12°E., 136 lks., no marks visible. (Record, 140 lks.)
A maple clump, 17 ins. diam., bears S.12°W., 69 lks., no marks visible.
An alder, 18 ins. diam., bears N.74°W., 48 lks., no marks visible. (Record, N.75¼°W.)
No other suitable trees available.

Fd BC on 2" IP as per M97-80 - by D McMahan 9/2021 - M179-78
Fd. BC on IP leaning South by W. White 11/2021 - M180-20