

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 218)

-----  
Set post, 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor., mkd: 1/4 S on W face; from which

A Fir, 40" dia., bears S.10°E., 6 lks., mkd: 1/4 S BT.

A Fir, 20" dia., bears N.34°E., 70 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11689)

-----  
Point for 1/4 sec. cor. of secs. 25 & 26, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3' long, 1" dia., 10" in the ground to solid rock, and in a mound of stone, 3 ft. base to top, with brass cap marked:

1/4

S 26 S 25  
1951

from which

A Fir, 9" dia., bears N.36°E., 15 lks., mkd: 1/4 S25 BT.

A Fir, 36" dia., bears S.55 1/2°W., 39 lks., mkd: 1/4 S26 BT.

Fd. & used on BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group # 1168, surveyed Sept./Dec. 1983 - (DCSO records Vol. 47 Page(s) 17829)