

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 221)

Set post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on W face; from which

A Fir, 20" dia., bears N.10°E., 50 lks., mkd: ¼ S BT.

A Fir, 15" dia., bears S.20°W., 60 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11691)

Point for the ¼ sec. cor. of secs. 23 & 24, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 23 S 24
1951

from which

A Fir, 8" dia., bears S.58°E., 41 lks., mkd: ¼ S24 BT.

A Maple, 14" dia., bears N.2½°W., 45 lks., mkd: ¼ S23 BT.