TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 221)

Set post, 4½ ft. long, 4" sq., 24" in the ground, for cor. of secs. 13, 14, 23, & 24, marked T20S S13 on NE, R10W S25 on SE, S23 SW, S14 on NW faces, 3 notches on S and 1 notch on E edges; from which

A Fir, 20" dia., bears N.21½°E., 40 lks., mkd: T20S R10W S13 BT.
A Fir, 24" dia., bears S.10°E., 10 lks., mkd: T20S R10W S24 BT.
A Fir, 18" dia., bears S.21°W., 18 lks., mkd: T20S R10W S23 BT.
A Fir, 20" dia., bears N.45°W., 25 lks., mkd: T20S R10W S14 BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11692)

Point for the cor. of secs. 13, 14, 23, & 24, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S R10W
S 14 | S 13
S 23 | S 24
1951

from which

A Cedar, 40" dia., bears N.70°E., 8 lks., mkd: T20S R10W S13 BT.
A Fir, 30" dia., bears *N.78°45'E., 176 lks., mkd: T20S R10W S24 BT.
A Fir, 60" dia., bears N.78°W., 160 lks., mkd: T20S R10W S14 BT.

The sec. cor. is located at the top of a bluff, 50 ft. high, facing NE. There is not suitable BT available to the SW.
* Per research 3/25/1999 BLM's micro fiche does have a NE bearing and sec. 24. DCSO JC

Stephen Stys - For: Roseburg Resources Co. - 3/2024 - M184-18

No monument was found.
BT fd (1951 rec. 60" Fir) bears N.78°31'33"W., 105.6' (rec. N.78°W.)
BT fd (1951 rec. 40" Cedar) bears N.69°25'20"E., 5.30' (rec. N.70°E.)