

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 222-3)

Set post, 4 ft. long, 3½" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on W face; from which

A Hemlock, 10" dia., bears N.47°W., 70 lks., mkd: ¼ S BT.

A Fir, 8" dia., bears S.15°W., 80 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11694)

Point for the ¼ sec. cor. of secs. 13 & 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 14 S 13
1952

from which

A Fir, 18" dia., bears N.65°45'E., 22 lks., mkd: ¼ S13 BT.

A Cedar, 28" dia., bears N.16¼°W., 57 lks., mkd: ¼ S14 BT.