

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 223)

-----  
Set post, 4½ ft. long, 4" sq., 24" in the ground, for cor. of secs. 11, 12, 13, & 14, marked T20S S12 on NE, R10W S13 on SE, S14 SW, S11 on NW faces, 4 notches on S and 1 on E edges; from which

- A Maple, 6" dia., bears N.21°E., 63 lks., mkd: T20S R10W S12 BT.
- A Fir, 16" dia., bears S.21°E., 73 lks., mkd: T20S R10W S13 BT.
- A Hemlock, 12" dia., bears S.54°W., 90 lks., mkd: T20S R10W S14 BT.
- A Chittem, 4" dia., bears N.64°W., 80 lks., mkd: T20S R10W S11 BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11694)

-----  
Point for the cor. of secs. 11, 12, 13, & 14, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S R10W

S 11 S 12  
S 14 S 13  
1952

from which

- A Hemlock, 20" dia., bears N.23¼°E., 74 lks., mkd: T20S R10W S12 BT.
- A Fir, 60" dia., bears S.46°45'E., 43 lks., mkd: T20S R10W S13 BT.
- A Hemlock, 10" dia., bears S.36°W., 45 lks., mkd: T20S R10W S14 BT.
- A Hemlock, 12" dia., bears N.18½°W., 46 lks., mkd: T20S R10W S11 BT.