

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 224)

Set post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on W face; from which

A Cedar, 6" dia., bears S.36°E., 69 lks., mkd: ¼ S BT.

A Maple, 7" dia., bears N.40°W., 60 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11696)

Point for the ¼ sec. cor. of secs. 11 & 12, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 11 S 12
1952

from which

A Fir, 50" dia., bears S.17°E., 35 lks., mkd: ¼ S12 BT.

A Maple, 22" dia., bears S.28°W., 78 lks., mkd: ¼ S11 BT.