

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 225-26)

Set post, 4 ft. long, 3½" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on W face; from which

A Fir, 30" dia., bears N.59°W., 73 lks., mkd: ¼ S BT.

A Fir, 30" dia., bears S.63°E., 73 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11698-9)

Point for the ¼ sec. cor. of secs. 1 & 2, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
S 2 S 1
1952

from which

A Hemlock, 25" dia., bears N.42½°E., 52 lks., mkd: ¼ S1 BT.

A Maple, 18" dia., bears N.40°W., 26 lks., mkd: ¼ S2 BT.