

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T19-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 216)

-----

Set post 4½ ft. long, 4" sq., 24" in ground for cor. of secs. 1, 2, 35 and 36, marked T19S R10W S36 on NE.; T20S R10W S1 on SE.; S2 on SW.; S35 on NW. faces, 5 notches on W. and 1 on E. edges; from which a

- Fir 16" dia., bears N.18°E., 49 lks. dist. mkd. T19S R10W S36 BT.
- Alder 7" dia., bears S.80°E., 63 lks. dist. mkd. T20S R10W S1 BT.
- Chittem 6" dia., bears S.16°W., 100 lks. dist. mkd. T20S R10W S2 BT.
- Fir 12" dia., bears N.26°W., 50 lks. dist. mkd. T19S R10W S35 BT.

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 262)

"No corners are found between the cor. of secs. 4, 5, 32 and 33, and the cor. which I accept as cor. of Tps. 19 and 20 S., R 10 W., but I find a fairly continuous line of old blazes extending as far as this Tp. cor., but no further eastward."

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11685)

-----

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 16" in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T 19 S R 10 W
<u>      S 35 S 36</u>
S 2 S 1
T 20 S
1952

from which

- A Maple 16" dia., bears N.4½°E., 111 lks. dist. mkd. T19S R10W S36 BT.
- An Alder 16" dia., bears S.47°45'E., 25 lks. dist. mkd. T20S R10W S1 BT.
- An Alder 18" dia., bears S.17½°W., 63 lks. dist. mkd. T20S R10W S2 BT.
- A Fir 60" dia., bears N.7¼°W., 164 lks. dist., mkd. T19S R10W S35 BT.

(Cont. Next Page)

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T19-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Cor. is located at the West side of a sandstone boulder, 5x5x5 ft. in place, on the right bank of Bob Creek. Chisel a large X in stone, 1½ lks. E. of corner point.