

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 639100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 1 only, T21-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (Group #36) (surveyed 1919) - (DCSO records Vol. 1 Pgs 259-60) and (Dup. Pg. 1065)

-----  
Set an Iron post 3 ft. long, 1" dia., 26" in the ground for 1/4 sec. cor. of sec. 1 only, with brass cap mkd: 1/4-----

S 1  
1919

from which

- A Fir 48" dia., bears S.73°E., 27 lks. dist. mkd. 1/4 S1 BT
- A Hemlock 9" dia., bears S.36°W., 44 lks dist mkd. 1/4 S1 BT

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11665)

-----  
The 1/4 sec. cor., monumented with an iron post 1" dia., 6" above ground, firmly set, with brass cap mkd. in 1919, from which the 1919 bearing trees:

- A dead Fir 50" dia., bears S.74°E., 29 lks. dist., with traces of scribe marks remaining on blaze in bark. (Rec. description, S.73°E., 27 lks. dist.)
- A Hemlock 14" dia., bears S.37 1/4°W., 44 lks. dist. with old blaze healed. (Rec. brg. S.36°W.)

The old iron post is rusted nearly through; in its place, Set an iron post 3 ft. long, 1" dia., 28" in the ground with brass cap mkd.

1/4 S 1  
1951

from which a new bearing tree:

- A Hemlock 12" dia., bears S.33 1/2°E., 61 lks. dist. mkd. 1/4 S1 BT.

Deposit the old iron post at the base of the new iron post.

Jerry Estabrook - For: Roseburg Resources - 1/2022 - M180-48

-----  
Found - A 1" iron pipe with 2 1/2" brass cap (properly) mkd. Set steel post alongside.

A rotten 70" fir stump with no visible marks bears S.74°E., 19.14'.

New BTs- A 15" Hemlock, face scribed "X BT" with X-chop and tag bears N.8°E., 30.5' to a spike at side center

A 10" Hemlock, face scribed "N 1/4 S1 BT" with X-chop and tag bears S.58°E., 15.2' to a spike at side center.

Continued next page

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 639100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 1 only, T21-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An 11" Hemlock, face scribed "N¼ S1 BT" with X-chop and tag bears S.82°W., 23.2' to a spike at side center  
A 1" iron pipe with 2½" brass cap marked "¼ S36 1951" bears N.89°22'07"E., 75.47'.  
Lat and Long per GARMIN ETREX hand held GPS:  
N: 43°46'57.3" W: 123°50'20.6"