

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.B. Byars under contract #202, dated March 11, 1874 - (DCSO records Vol. 1 Page(s) 187)

Set a Fir post, 36" long, 5" sq., 18" in the ground, for ¼ secs. cor. mkd: ¼ sec corner; from which
A double Maple, 60" dia., bears S.50°E., 8 lks.
A double Maple, 20" dia., bears N.18°W., 40 lks.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11688)

Point for ¼ sec. cor. of secs. 25 & 36, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3' long, 1" dia., 28" in the ground, with brass cap marked:
¼ $\frac{S\ 25}{S\ 36}$
1951

from which
A Fir, 22" dia., bears N.63°E., 32 lks., mkd: ¼ S25 BT.
A Fir, 16" dia., bears S.80°E., 28 lks., mkd: ¼ S36 BT.

Fd. & used on BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group # 1168, surveyed Sept./Dec. 1983 - (DCSO records Vol. 47 Page(s) 17821)

Fd. Ok by R. Stuntzner, 10/1984 - M 97-80