TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 219)

Set post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on N face; from which
A Fir, 18" dia., bears N.30°E., 100 lks., mkd: ¼ S BT.
A Fir, 20" dia., bears S.53°W., 160 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11690)

Point for ¼ sec. cor. of secs. 24 & 25, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3' long, 1" dia., 28" in the ground, with brass cap marked:

¼ S 24 / S 25 / 1951

from which
A Fir, 64" dia., bears N.73°W., 64 lks., mkd: ¼ S24 BT.
A Hemlock, 16" dia., bears S.55°E., 42½ lks., mkd: ¼ S25 BT.

Fd. & used on BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group # 1168, surveyed Sept./Dec. 1983 - (DCSO records Vol. 47 Page(s) 17827-28)

Stephen Stys - For: Roseburg Resources Co. - 3/2024 - M184-18

Found - A 2½" brass cap on a 1" iron pipe as set per dcso records vol. 27, page 11690 and (properly) mkd.
A 28" Hemlock stump, with healed face bears S.55°E., 28.0' (per DCSO records VOL. 27, PAGE 11690).
A 64" Fir snag, with healed face and tag bears N.73°W., 42.2' (per DCSO rec VOL. 27, Pg 11690)
New BOs- A steel post bears North 2.0' a steel post bears East 2.0'
New BTs- A 13" alder, bark scribed "N¼ S25 BT" with X-chop & tag bears S.40°W. 15.2' to a spike at side center
A 20" Alder, bark scribed "S¼ S24 BT" with x-chop & tag bears N.70°W., 9.0' to a spike at side center
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS:
N:43°48'36.4" W:123°50'22.1".