TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 222)

Set post, 4 ft. long, 3½ sq., 24 in the ground for ¼ sec. cor., mkd: ¼ S on N face; from which
A Fir, 18" dia., bears N.10°E., 60 lks., mkd: ¼ S BT.
A Fir, 10" dia., bears S.20°W., 80 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11692-93)

Point for the ¼ sec. cor. of secs. 13 & 24, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft long, 1" dia., 28" in the ground with brass cap marked:

¼ S 13 / S 24 1952

from which
A Cedar, 34" dia., bears N.28°W., 24½ lks., mkd: ¼ S13 BT.
A Cedar, 36" dia., bears S.56½°W., 66 lks., mkd: ¼ S24 BT.

Stephen Stys - For: Roseburg Resources Co. - 3/2024 - M184-18

Fd f1" pipe with 2½" brass cap as set DCSO records Vol. 27, Pg 11692-11693