

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 223-24)

Set post, 4 ft. long, 4" sq., 24" in the ground for 1/4 sec. cor., mkd: 1/4 S on N face; from which

A Fir, 36" dia., bears N.73°E., 120 lks., mkd: 1/4 S BT.

A Hemlock, 20" dia., bears S.80°W., 200 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11695)

Point for the 1/4 sec. cor. of secs. 12 & 13, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

1/4 S 12
S 13
1952

from which

A Cedar, 42" dia., bears N.73°W., 62 lks., mkd: 1/4 S12 BT.

A Cedar, 52" dia., bears S.19°W., 56 lks., mkd: 1/4 S13 BT.