

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 225)

Set post, 4 ft. long, 3½" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on N face; from which

A Chittem, 4" dia., bears N.45°W., 70 lks., mkd: ¼ S BT.

A Dogwood, 5" dia., bears S.70°E., 90 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11697-8)

Point for the ¼ sec. cor. of secs. 1 & 12, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ $\frac{S \ 1}{S \ 12}$
1952

from which

A Cedar, 13" dia., bears N.44¼°E., 29 lks., mkd: ¼ S1 BT.

A Fir, 14" dia., bears S.35°E., 32 lks., mkd: T20S R10W S12 BT.