

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25; 19 & 30, T20-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 201)

-----  
Set a sandstone 20x18x12 ins., 15" in the ground, for cor. to secs. 19, 24, 25 and 30, marked with 2 notches on S. and 4 notches on N. edges; from which

A Maple 18" dia., bears N.87°E., 94 lks. dist. mkd. T20S R9W S19 BT.

A Fir 50" dia., bears N.3½°W., 53 lks. dist. mkd. T20S R10W S24 BT.

A Maple 15" dia., bears S.30°W., 75 lks. dist. mkd. T20S R10W S25 BT.

A Cedar 27" dia., bears S.3°E., 225 lks. dist. mkd. T20S R9W S30 BT.

Cor. Fd. OK in GL0 survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 219)

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11674-75)

-----  
The sec. cor., monumented with a sandstone 16x10x6 ins., firmly set 10" in the ground, mkd. with 2 notches on S. edge, from which the remaining original bearing trees:

A Fir 66" dia., bears N.3°E., 45 lks. dist., with the scribe marks T20S R10W S24 BT plainly visible on bark blaze. (Rec. desc., N.3½°W., 53 lks.)

A Maple 36" dia., bears N.85°E., 94 lks. dist. with no marks remaining on decayed blaze. (Rec. brg. N.87°E.)

A Cedar 50" dia., bears S.0°45'E., 211 lks. dist., plainly blazed and healed. (Rec. brg. & dist., S.3°E., 225 lks.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S	
R 10 W	R 9 W
S 24	S 19
S 25	S 30
1951	

from which new bearing trees:

A Maple 26" dia., bears S.36½°W., 85 lks. dist. mkd. T20S R10W S25 BT.

A Cascara 6" dia., bears N.75½°W., 11 lks. dist. mkd. T20S R10W S24 BT.

Deposit the marked stone alongside the iron post.

continued next page

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec Cor for 24 & 25; 19 & 30, T20-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Stephen Stys - For: Roseburg Resources Co. - 3/2024 - M184-18

-----  
Found - A 2½" brass cap on a 2" iron pipe as set per record (Properly) mkd. A 1/2" iron pipe 3' tall sits alongside monument. Set steel post alongside monument.

No record BTs found for this corner.

New BTs- A 17" maple, bark scribed "SW S19 BT" with X-chop and tag bears N.25°E., 21.7' to a spike at side center.

A 21" maple, bark scribed "SW S19 BT" with X-chop and tag bears N.52°E., 31.9' to a spike at side center.

A 27" Maple, faced & scribed "NE S25 BT" with X-chop and tag bears S.6°W., 20.7' to a spike at side center.

A 12" fir, faced & scribed "SE S24 BT" with X-chop and tag bears N.81°W., 12.8' to a spike at side center.

LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS:  
N: 43°48'37.0" W: 123°49'47.7".