

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 700542

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only, T20-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 210-11)

Set post 4 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor. mkd. 1/4 S on W. face; from which a
Chittem 4" dia., bears N.20°E., 82 lks. dist. mkd. 1/4 S BT
Dogwood 5" dia., bears S.30°W., 73 lks. dist. mkd. 1/4 S BT

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 268)

Set an Iron post 3 ft. long, 1" dia., 27" in the ground for 1/4 sec. cor. of sec. 7 only, with brass cap mkd. 1/4 S 7
1921

from which
An Alder 20" dia., bears N.68°E., 55 lks. mkd. 1/4 S7 BT.
A Maple 12" dia., bears S.50°E., 39 lks. mkd. 1/4 S7 BT.

Fd. OK and used in BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11679)

BLM corrective remonumentation/rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO recs Vol. 58 Pgs 23084-5)

The 1/4 sec. cor. of sec. 7 only, monumented with an iron pipe, 1" dia., firmly set, projecting 2" above ground, with concrete core and brass cap missing, from which the remains of a bearing tree mkd. by Mensch in 1921-22

A maple clump, bears S.50°E., 25.7 ft., no marks visible.
At the Corner Point
Set a stainless steel post, 28" long, 2 1/2" dia., 25" in the ground, directly over iron pipe, with brass cap mkd.

T20S | T20S
R10W | R9W
1/4 S 7
2006

from which a new bearing trees
A fir, 12" dia., bears N.26°E., 16.9 ft., mkd. 1/4 S7 BT.
A maple, 6" dia., in the center of a clump, bears S.48 1/2°E., 26.0 ft., mkd. 1/4 S7 BT and a Mag Nail on the left side center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

cont.

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 700542

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only, T20-9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Jerry Estabrook - For: Roseburg Resources Co. - 5/2021 - M179-43

Found - A 2½" stainless steel pipe w/3½" brass cap mkd "T20S R10W T20S R9W 1/4 S7 2006" per DCS0 recs VOL. 58 Pgs 23084-23085. Set steel post along side.

FD BTs- An 18" fir with healed face and tag N.26°E., 16.9'.
A 6" Maple with visible scribe in face and tag bears S.48°30'E., 26.0'.

New BT - A 26" Maple, face scribed "X BT" with X-chop and tag bears S.16°W., 20.1' to a spike at side center.

LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS (not survey grade) N: 43°50'53.7" W: 123°49'41.7"